

Pressure Temperature Charts



°F	°C	R-236fa
-40	-40.0	-12.6
-35	-37.2	-12.2
-30	-34.4	-11.8
-25	-31.7	-11.3
-20	-28.9	-10.7
-15	-26.1	-10.1
-10	-23.3	-9.3
-5	-20.6	-8.5
0	-17.8	-7.6
5	-15.0	-6.6
10	-12.2	-5.5
15	-9.4	-4.3
20	-6.7	-2.9
25	-3.9	-1.4
30	-1.1	0.2
35	1.7	2.0
40	4.4	4.0
45	7.2	6.1
50	10.0	8.5
55	12.8	11.0

°F	°C	R-236fa
60	15.6	13.7
65	18.3	16.7
70	21.1	19.9
75	23.9	23.3
80	26.7	27.0
85	29.4	30.9
90	32.2	35.2
95	35.0	39.7
100	37.8	44.6
105	40.6	49.7
110	43.3	55.2
115	46.1	61.1
120	48.9	67.3
125	51.7	73.8
130	54.4	80.8
135	57.2	88.2
140	60.0	96.0
145	62.8	104.2
150	65.6	112.9

Vapor Pressure in PSIG

Refrigerant Boiling Point

Refrigerant:	Components:	BP (0 PSIG):
R-236fa	R-236fa (100%) 1,1,1,3,3,3-Hexafluoropropane	29.3°F

Liquid Density

Refrigerant:	Liquid Density:	-80°F	-40°F	0°F	40°F	80°F	120°F
R-236fa	lb/cu. ft.	101.3	97.4	93.4	89.1	84.5	79.5
	lb/gal.	13.5	13.0	12.5	11.9	11.3	10.6

Physical Properties

	R236fa
Environmental Classification	HFC
Molecular Weight	152.04 g/mol
Boiling Point (1atm, °F)	29.3
Critical Pressure (psia)	464.1
Critical Temperature (°F)	256.9
Critical Density (lb./ft ³)	34.4
Vapor Density (bp, lb./ft ³)	0.4
Liquid Heat of Vaporization (bp, BTU/lb.)	85.3
Ozone Depletion Potential (CFC 11 - 1.0)	0
Global Warming Potential (CO ₂ = 1.0)	8060
ASHRAE Standard 34 Safety Rating	A1